


PX0843/A Datasheet

 [View Product Page](#)

Product Name // Front Panel Mount Leaded USB 2.0 Connector PX0843 Series Sealed A Socket Front of Panel to 5 Way Crimp Connector



// Product Description:

- Front Panel Mounting Leaded Connector
 - Water and dustproof to IP68 when mated with compatible connector
 - Sealed Standard USB 2.0 Type A socket to 125mm long cable terminated in 5 way crimp connector to use with PC header
- PX0733 Sealing Cap available separately to maintain IP rating of unmated connectors
 - Mate with PX0840, PX0841 USB Cables

// General Information:

Product Display Title:	Front Panel Mount Leaded Connector
Product Family:	Circular Data Connectors
Product Series:	Standard Buccaneer - USB
Body Colour:	Black
Body Material:	Polyester (PE) - Glass Filled
Body Material Type:	Plastic Body
Contact Type:	Socket Contact
Coupling Type:	Screw
Current Max:	1A
Data Cable Type:	USB 2.0 Sealed A Socket to 5 Way Crimp
Diameter Over Coupling Ring Mm:	38.1mm
Flamability Rating:	UL94V-0
Function:	Front Panel Mount Connector
Ip Rating:	IP68, IP69K
Max Operating Temperature:	+70°C
Min Operating Temperature:	0°C
Number Of Contacts:	4 Contacts
Rohs Compliant:	Yes
Voltage Max:	5V

// Product PDF Links

 [Standard Series USB connectors...](#)

// Product 3D CAD Model Links

 [PX0843/A3D CAD Model](#)