


PXP0025/C/1M00/A Datasheet

**Product Name // Miniature Plastic Rear Panel Mount USB
C Female to USB A Male Cable Assembly 1m**

 [View Product Page](#)



// **Product Description:**

- IP67 Female USB C to Male USB A 3.0
 - IP67 when fitted with Miniature Sealing Cap
 - Overall aluminium+polyester shield plus tinned copper braid shield
- USB 3.0 Performance
 - length 1m

// **General Information:**

Product Display Title:	Rear Panel Mount Leaded Connector
Product Family:	Circular Data Connectors
Product Series:	20 Series USB
Body Colour:	Black
Body Material:	PVC
Body Material Type:	Plastic Body
Cable Length:	1m
Contact Pin Material:	Copper, Gold plated
Contact Type:	Socket Contact
Coupling Type:	Screw
Data Cable Type:	USB 3.0 Sealed C Socket to Standard A Plug
Durability:	10,000
Fixing Nut Material:	Plastic
Flamability Rating:	UL94V-0
Function:	Rear Panel Mount Connector
Ip Rating:	IP67
Max Operating Temperature:	80°C
Min Operating Temperature:	-20°C
Max Panel Thickness:	2.5mm
Number Of Contacts:	12 Contacts
Panel Cut Out:	16.0mm x 15.0mm
Rohs Compliant:	Yes
Sheath Colour:	Black
Sheath Material:	PVC
Thread Size:	5/8-27UN-2A
Voltage Max:	20V

// **Product PDF Links**

 [20 Series USB Waterproof product...](#)

// **Product 3D CAD Model Links**

 [PXP0025/C/1M00/A3D CAD Model](#)



Have a question or project enquiry
you'd like to talk to us about?



[Click Here To Contact Us](#)