

## Specification Sheet

Part Number: TSR1W-21

Tamper resistant, self-locking hidden positive latch permits quick re-entry as well as providing a secure installation of premise wire.

Fittings incorporate a minimum 1" bend radius per ANSI/TIA-568-C and 569-A standards.

Rubber-based, foam-tape adhesive with high ultimate bond strength conforms to any surface.

Flexible hinge allows the raceway to endure numerous openings without creating discoloration or stress cracking



Tee Cover, 1" Bend Radius, PVC, White, 1/bg

|                |           |
|----------------|-----------|
| Article Number | 250-01212 |
|----------------|-----------|

|      |         |
|------|---------|
| Type | TSR1-21 |
|------|---------|

|       |            |
|-------|------------|
| Color | White (WH) |
|-------|------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                     |                                                                                                                                                                                                                                                                              |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | HellermannTyton's low voltage raceway (TSR) is a one piece, non-metallic, adhesive backed, latching raceway designed to aesthetically organize and route communications wires, including high speed UTP cable and fiber optic cable, from the telecom room to the work area. |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                             |
|-------------------|---------------------------------------------|
| Short Description | Tee Cover, 1" Bend Radius, PVC, White, 1/bg |
|-------------------|---------------------------------------------|

|                  |                |
|------------------|----------------|
| Global Part Name | TSR1-21-PVC-WH |
|------------------|----------------|

|                     |       |
|---------------------|-------|
| Length L (Imperial) | 2.339 |
|---------------------|-------|

|                   |       |
|-------------------|-------|
| Length L (Metric) | 59.41 |
|-------------------|-------|

|                    |       |
|--------------------|-------|
| Width W (Imperial) | 3.775 |
|--------------------|-------|

|                  |       |
|------------------|-------|
| Width W (Metric) | 95.89 |
|------------------|-------|

|                     |       |
|---------------------|-------|
| Height H (Imperial) | 0.607 |
|---------------------|-------|

|                   |       |
|-------------------|-------|
| Height H (Metric) | 15.42 |
|-------------------|-------|

|                              |       |
|------------------------------|-------|
| Wall Thickness WT (Imperial) | 0.055 |
|------------------------------|-------|

|                            |      |
|----------------------------|------|
| Wall Thickness WT (Metric) | 1.40 |
|----------------------------|------|

|          |                         |
|----------|-------------------------|
| Material | Polyvinylchloride (PVC) |
|----------|-------------------------|

|                   |     |
|-------------------|-----|
| Material Shortcut | PVC |
|-------------------|-----|

|              |           |
|--------------|-----------|
| Flammability | UL 94 V-0 |
|--------------|-----------|

|              |    |
|--------------|----|
| Halogen Free | No |
|--------------|----|

|                       |    |
|-----------------------|----|
| UV Resistant (Yes/No) | No |
|-----------------------|----|

|                |                     |
|----------------|---------------------|
| Use Conditions | For Indoor Use Only |
|----------------|---------------------|

|                       |                |
|-----------------------|----------------|
| Operating Temperature | +122°F (+50°C) |
|-----------------------|----------------|

|                              |    |
|------------------------------|----|
| Reach Compliant (Article 33) | No |
|------------------------------|----|

|                |     |
|----------------|-----|
| ROHS Compliant | Yes |
|----------------|-----|

|                             |   |
|-----------------------------|---|
| Package Quantity (Imperial) | 1 |
|-----------------------------|---|

|                           |   |
|---------------------------|---|
| Package Quantity (Metric) | 1 |
|---------------------------|---|

|                |            |
|----------------|------------|
| Customs Number | 3925900000 |
|----------------|------------|

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)