

Specification Sheet

Part Number: TSR2W-21

Tamper resistant, self-locking hidden positive latch permits quick re-entry as well as providing a secure installation of premise wire.

Fittings incorporate a minimum 1" bend radius per ANSI/TIA-568-C and 569-A standards.

Rubber-based, foam-tape adhesive with high ultimate bond strength conforms to any surface.

Flexible hinge allows the raceway to endure numerous openings without creating discoloration or stress cracking



Tee Cover, 1-1/4", 1" Bend Radius, PVC, White, 1/bg

Article Number 250-02212

Type TSR2-21

Color White (WH)

Quantity Per pack

Product Description HellermannTyton's low voltage raceway (TSR) is a one piece, non-metallic, adhesive backed, latching raceway designed to aesthetically organize and route communications wires, including high speed UTP cable and fiber optic cable, from the telecom room to the work area.

Short Description Tee Cover, 1-1/4", 1" Bend Radius, PVC, White, 1/bg

Global Part Name TSR2-21-PVC-WH

Length L (Imperial) 2.854

Length L (Metric) 72.49

Width W (Imperial) 4.270

Width W (Metric) 108.46

Height H (Imperial) 0.885

Height H (Metric) 22.48

Wall Thickness WT (Imperial) 0.070

Wall Thickness WT (Metric) 1.78

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability UL 94 V-0

Halogen Free No

UV Resistant (Yes/No) No

Use Conditions For Indoor Use Only

Operating Temperature +122°F (+50°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Package Quantity (Imperial) 1

Package Quantity (Metric) 1

Customs Number 3925900000

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)