

# Self-Protected High Side Driver with Temperature and Current Limit

## NCV8450, NCV8450A

The NCV8450/A is a fully protected High-Side Smart Discrete device with a typical  $R_{DS(on)}$  of  $1.0\ \Omega$  and an internal current limit of  $0.8\ A$  typical. The device can switch a wide variety of resistive, inductive, and capacitive loads.

### Features

- Short Circuit Protection
- Thermal Shutdown with Automatic Restart
- Overvoltage Protection
- Integrated Clamp for Inductive Switching
- Loss of Ground Protection
- ESD Protection
- Slew Rate Control for Low EMI
- Very Low Standby Current
- NCV Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q100 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

### Typical Applications

- Automotive
- Industrial


### PRODUCT SUMMARY

| Symbol       | Characteristics        | Value    | Unit     |
|--------------|------------------------|----------|----------|
| $V_{IN\_CL}$ | Overvoltage Protection | 54       | V        |
| $V_{D(on)}$  | Operation Voltage      | 4.5 – 45 | V        |
| $R_{on}$     | On-State Resistance    | 1.0      | $\Omega$ |



SOT-223  
(TO-261)  
CASE 318E

### MARKING DIAGRAM



XXXXX = V8450 or 8450A  
A = Assembly Location  
Y = Year  
W = Work Week  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 8 of this data sheet.

# NCV8450, NCV8450A




Figure 1. Block Diagram

## PACKAGE PIN DESCRIPTION

| Pin # | Symbol         | Description               |
|-------|----------------|---------------------------|
| 1     | IN             | Control Input, Active Low |
| 2     | V <sub>D</sub> | Supply Voltage            |
| 3     | OUT            | Output                    |
| 4     | V <sub>D</sub> | Supply Voltage            |

# NCV8450, NCV8450A

## MAXIMUM RATINGS

| Rating                                                                                                                                                               | Symbol         | Value |                    | Unit             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------|--------------------|------------------|
|                                                                                                                                                                      |                | Min   | Max                |                  |
| DC Supply Voltage (Note 1)                                                                                                                                           | $V_D$          | -16   | 45                 | V                |
| Load Dump Protection<br>( $R_I = 2\ \Omega$ , $t_d = 400\text{ ms}$ , $V_{IN} = 0, 10\text{ V}$ , $I_L = 150\text{ mA}$ , $V_{bb} = 13.5\text{ V}$ )                 | $V_{LoadDump}$ |       | 85                 | V                |
| Input Current                                                                                                                                                        | $I_{in}$       | -15   | 15                 | mA               |
| Output Current (Note 1)                                                                                                                                              | $I_{out}$      |       | Internally Limited | A                |
| Total Power Dissipation<br>@ $T_A = 25^\circ\text{C}$ (Note 2)<br>@ $T_A = 25^\circ\text{C}$ (Note 3)                                                                | $P_D$          |       | 1.13<br>1.60       | W                |
| Electrostatic Discharge (Note 4)<br>(Human Body Model (HBM) 100 pF/1500 $\Omega$ )<br>Input<br>All other                                                             |                |       | 1<br>5             | kV               |
| Single Pulse Inductive Load Switching Energy (Note 4)<br>( $V_{DD} = 13.5\text{ V}$ , $I = 465\text{ mA}$ , $L = 200\text{ mH}$ , $T_{JStart} = 150^\circ\text{C}$ ) | $E_{AS}$       |       | 29                 | mJ               |
| Operating Junction Temperature                                                                                                                                       | $T_J$          | -40   | +150               | $^\circ\text{C}$ |
| Storage Temperature                                                                                                                                                  | $T_{storage}$  | -55   | +150               | $^\circ\text{C}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

- Reverse Output current has to be limited by the load to stay within absolute maximum ratings and thermal performance.
- Minimum Pad.
- 1 in square pad size, FR-4, 1 oz Cu.
- Not subjected to production testing.

## THERMAL RESISTANCE RATINGS

| Parameter                                                                                   | Symbol                             | Max Value   | Unit |
|---------------------------------------------------------------------------------------------|------------------------------------|-------------|------|
| Thermal Resistance (Note 5)<br>Junction-to-Ambient (Note 2)<br>Junction-to-Ambient (Note 3) | $R_{\theta JA}$<br>$R_{\theta JA}$ | 110<br>78.3 | K/W  |

- Not subjected to production testing.




Figure 2. Applications Test Circuit

# NCV8450, NCV8450A

## ELECTRICAL CHARACTERISTICS ( $6 \leq V_D \leq 45 \text{ V}$ ; $-40^\circ\text{C} < T_J < 150^\circ\text{C}$ unless otherwise specified)

| Rating | Symbol | Conditions | Value |     |     | Unit |
|--------|--------|------------|-------|-----|-----|------|
|        |        |            | Min   | Typ | Max |      |

### OUTPUT CHARACTERISTICS

|                                           |                     |                                                                                                                                                                                                                                                                                                           |     |                   |               |               |
|-------------------------------------------|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-------------------|---------------|---------------|
| Operating Supply Voltage                  | $V_{\text{SUPPLY}}$ |                                                                                                                                                                                                                                                                                                           | 4.5 | –                 | 45            | V             |
| On Resistance<br>(Pin 1 Connected to GND) | $R_{\text{ON}}$     | $T_J = 25^\circ\text{C}$ , $I_{\text{OUT}} = 150 \text{ mA}$ , $V_D = 7 \text{ V} - 45 \text{ V}$<br>$T_J = 150^\circ\text{C}$ , $I_{\text{OUT}} = 150 \text{ mA}$ , $V_D = 7 \text{ V} - 45 \text{ V}$<br>(Note 6)<br>$T_J = 25^\circ\text{C}$ , $I_{\text{OUT}} = 150 \text{ mA}$ , $V_D = 6 \text{ V}$ |     | 1.0<br>1.4<br>1.1 | 2<br>3<br>2.1 | $\Omega$      |
| Standby Current (Pin 1 Open)              | $I_D$               | $V_D \leq 20 \text{ V}$<br>$V_D > 20 \text{ V}$                                                                                                                                                                                                                                                           |     | 0.6               | 10<br>100     | $\mu\text{A}$ |

### INPUT CHARACTERISTICS

|                                              |                      |                                                                                                                                                                                      |            |     |   |               |
|----------------------------------------------|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-----|---|---------------|
| Input Current – Off State                    | $I_{\text{IN\_OFF}}$ | $V_{\text{OUT}} \leq 0.1 \text{ V}$ , $R_L = 270 \Omega$ , $T_J = 25^\circ\text{C}$<br>$V_{\text{OUT}} \leq 0.1 \text{ V}$ , $R_L = 270 \Omega$ , $T_J = 150^\circ\text{C}$ (Note 6) | –50<br>–40 |     |   | $\mu\text{A}$ |
| Input Current – On State<br>(Pin 1 Grounded) | $I_{\text{IN\_ON}}$  |                                                                                                                                                                                      |            | 1.5 | 3 | mA            |
| Input Resistance (Note 6)                    | $R_{\text{IN}}$      |                                                                                                                                                                                      |            | 1   |   | k $\Omega$    |

### SWITCHING CHARACTERISTICS

|                                                                                                  |                      |                                                                                                       |  |     |            |                  |
|--------------------------------------------------------------------------------------------------|----------------------|-------------------------------------------------------------------------------------------------------|--|-----|------------|------------------|
| Turn-On Time (Note 7)<br>( $V_{\text{IN}} = V_D$ to 0 V) to 90% $V_{\text{OUT}}$                 | $t_{\text{ON}}$      | $R_L = 270 \Omega$ (Note 6)<br>$V_D = 13.5 \text{ V}$ , $R_L = 270 \Omega$ , $T_J = 25^\circ\text{C}$ |  | 30  | 125<br>100 | $\mu\text{s}$    |
| Turn-Off Time (Note 7)<br>( $V_{\text{IN}} = 0 \text{ V}$ to $V_D$ ) to 10% $V_{\text{OUT}}$     | $t_{\text{OFF}}$     | $R_L = 270 \Omega$ (Note 6)<br>$V_D = 13.5 \text{ V}$ , $R_L = 270 \Omega$ , $T_J = 25^\circ\text{C}$ |  | 60  | 175<br>150 | $\mu\text{s}$    |
| Slew Rate On (Note 7)<br>( $V_{\text{IN}} = V_D$ to 0V) 10% to 30% $V_{\text{OUT}}$              | $dV/dt_{\text{ON}}$  | $R_L = 270 \Omega$ (Note 6)<br>$V_D = 13.5 \text{ V}$ , $R_L = 270 \Omega$ , $T_J = 25^\circ\text{C}$ |  | 0.7 | 4<br>4     | V/ $\mu\text{s}$ |
| Slew Rate Off (Note 7)<br>( $V_{\text{IN}} = 0 \text{ V}$ to $V_D$ ) 70% to 40% $V_{\text{OUT}}$ | $dV/dt_{\text{OFF}}$ | $R_L = 270 \Omega$ (Note 6)<br>$V_D = 13.5 \text{ V}$ , $R_L = 270 \Omega$ , $T_J = 25^\circ\text{C}$ |  | 0.9 | 4<br>4     | V/ $\mu\text{s}$ |

### OUTPUT DIODE CHARACTERISTICS (Note 6)

|                                  |       |                                   |  |     |     |   |
|----------------------------------|-------|-----------------------------------|--|-----|-----|---|
| Drain-Source Diode Voltage       | $V_F$ | $I_{\text{OUT}} = -0.2 \text{ A}$ |  | 0.6 |     | V |
| Continuous Reverse Drain Current | $I_S$ | $T_J = 25^\circ\text{C}$          |  |     | 0.2 | A |

### PROTECTION FUNCTIONS (Note 8)

|                                                                                                     |                       |                                                                                                                                                                                                                                                               |     |     |     |                  |
|-----------------------------------------------------------------------------------------------------|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-----|-----|------------------|
| Temperature Shutdown (Note 6)                                                                       | $T_{\text{SD}}$       |                                                                                                                                                                                                                                                               | 150 | 175 | –   | $^\circ\text{C}$ |
| Temperature Shutdown Hysteresis (Note 6)                                                            | $T_{\text{SD\_HYST}}$ |                                                                                                                                                                                                                                                               |     | 5   |     | $^\circ\text{C}$ |
| Output Current Limit                                                                                | $I_{\text{LIM}}$      | $T_J = -40^\circ\text{C}$ , $V_D = 13.5 \text{ V}$ , $t_m = 100 \mu\text{s}$ (Note 6)<br>$T_J = 25^\circ\text{C}$ , $V_D = 13.5 \text{ V}$ , $t_m = 100 \mu\text{s}$<br>$T_J = 150^\circ\text{C}$ , $V_D = 13.5 \text{ V}$ , $t_m = 100 \mu\text{s}$ (Note 6) | 0.5 | 0.8 | 1.5 | A                |
| Output Clamp Voltage<br>(Inductive Load Switch Off)<br>At $V_{\text{OUT}} = V_D - V_{\text{CLAMP}}$ | $V_{\text{CLAMP}}$    | $I_{\text{OUT}} = 4 \text{ mA}$                                                                                                                                                                                                                               | 45  | 52  |     | V                |
| Overvoltage Protection                                                                              | $V_{\text{IN\_CL}}$   | $I_{\text{CLAMP}} = 4 \text{ mA}$                                                                                                                                                                                                                             | 50  | 54  |     | V                |

6. Not subjected to production testing

7. Only valid with high input slew rates

8. Protection functions are not designed for continuous repetitive operation and are considered outside normal operating range

TYPICAL CHARACTERISTIC CURVES




Figure 3.  $R_{DS(on)}$  vs. Temperature




Figure 4.  $R_{DS(on)}$  vs. Output Load




Figure 5.  $R_{DS(on)}$  vs.  $V_D$




Figure 6. Turn On Time vs. Temperature




Figure 7. Turn Off Time vs. Temperature




Figure 8. Slew Rate (ON) vs. Temperature

TYPICAL CHARACTERISTIC CURVES




Figure 9. Slew Rate (OFF) vs. Temperature




Figure 10. Current Limit vs. Temperature




Figure 11. Peak Short Circuit Current vs.  $V_D$  Voltage




Figure 12.  $V_D$  Leakage Current vs. Temperature Off-State




Figure 13.  $V_D$  Leakage Current vs.  $V_D$  Voltage Off-State




Figure 14. On-State Input Current vs. Temperature

TYPICAL CHARACTERISTIC CURVES




Figure 18. Input Current vs.  $V_D$  Voltage Off-State




Figure 15. Output Voltage vs.  $V_D$  Voltage




Figure 16. Input Current vs.  $V_D$  Voltage On-State




Figure 17. Single Pulse Maximum Switch-off Current vs. Load Inductance




Figure 19. Initial Short-Circuit Shutdown Time vs. Temperature

# NCV8450, NCV8450A

## TYPICAL CHARACTERISTIC CURVES




Figure 20.  $R_{\theta JA}$  vs. Copper Area




Figure 21. Transient Thermal Response

### ISO PULSE TEST RESULTS

| Test Pulse | Test Level | Test Results | Pulse Cycle Time and Generator Impedance |
|------------|------------|--------------|------------------------------------------|
| 1          | 200 V      | C            | 500 ms, 10 $\Omega$                      |
| 2          | 150 V      | C            | 500 ms, 10 $\Omega$                      |
| 3a         | 200 V      | C            | 100 ms, 50 $\Omega$                      |
| 3b         | 200 V      | C            | 100 ms, 50 $\Omega$                      |
| 5          | 175 V      | E(100 V)     | 400 ms, 2 $\Omega$                       |

### ORDERING INFORMATION

| Device        | Package           | Shipping <sup>†</sup> |
|---------------|-------------------|-----------------------|
| NCV8450STT3G  | SOT-223 (Pb-Free) | 4000 / Tape & Reel    |
| NCV8450ASTT3G | SOT-223 (Pb-Free) | 4000 / Tape & Reel    |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)