

Siemens  
EcoTech



LOGO! 24CE, logic module, display power supply / I/O: 24 V/24 V/24 V trans., 8 DI (4 AI)/4 DO, memory 400 blocks, modularly expandable, Ethernet integrated web server, data log, user-defined web pages, standard microSD card for LOGO! Soft Comfort V8.4 or higher, older projects executable cloud connection, MQTT in all LOGO! 8.4 basic units



Figure similar

<b>Display</b>	
with display	Yes
<b>Installation type/mounting</b>	
Mounting	on 35 mm DIN rail, 4 spacing units wide
<b>Supply voltage</b>	
Rated value (DC)	
• 24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
<b>Time of day</b>	
Time switching clocks	
• Number	400; Max. 400, function-specific
• Power reserve	480 h
<b>Digital inputs</b>	
Number of digital inputs	8; Of which 4 can be used in analog mode (0 to 10 V)
<b>Digital outputs</b>	
Number of digital outputs	4; Transistor
Short-circuit protection	Yes; electrical (1 A)
Output current	
• for signal "1" permissible range for 0 to 55 °C, max.	0.3 A
<b>EMC</b>	
Emission of radio interference acc. to EN 55 011	
• Limit class B, for use in residential areas	Yes; Radio interference suppression according to EN55011, Limit Value Class B
<b>Standards, approvals, certificates</b>	
Siemens Eco Profile (SEP)	Siemens EcoTech
CE mark	Yes
CSA approval	No; covered by UL cert
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes
Marine approval	Yes; in preparation
Ecological footprint	
• environmental product declaration	Yes
Global warming potential	

— global warming potential, (total) [CO2 eq]	51.5 kg
— global warming potential, (during production) [CO2 eq]	9.64 kg
— global warming potential, (during operation) [CO2 eq]	42.1 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.364 kg

#### Ambient conditions

Ambient temperature during operation	
• min.	-20 °C; No condensation
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 080 hPa ... 795 hPa (-1 000 m ... +2 000 m)

#### Dimensions

Width	71.5 mm
Height	90 mm
Depth	60 mm

#### Classifications

	Version	Classification
eClass	14	27-24-22-16
eClass	12	27-24-22-16
eClass	9.1	27-24-22-16
eClass	9	27-24-22-16
eClass	8	27-24-22-16
eClass	7.1	27-24-22-16
eClass	6	27-24-22-16
ETIM	10	EC001417
ETIM	9	EC001417
ETIM	8	EC001417
ETIM	7	EC001417

#### Approvals / Certificates

##### General Product Approval



[Manufacturer Declaration](#)



[KC](#)

##### For use in hazardous locations



[FM](#)



##### Maritime application

##### Maritime application

[NK / Nippon Kaiji Kyokai](#)

[CCS \(China Classification Society\)](#)



##### Environment

last modified:

5/16/2025