

## VT CTL

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)



The fully insulated plastic housings of our continuity testers are shockproof and unbreakable, making these instruments ideal for daily use, even in tough conditions. The integrated torch makes it easier to locate defective cables quickly and safely. The results of the continuity test can be conveyed visually and acoustically.

### General ordering data

Version	Testing tools, Testing device
Order No.	<a href="#">2436690000</a>
Type	VT CTL
GTIN (EAN)	4050118450040
Qty.	1 items

**VT CTL**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data**

**Approvals**

Approvals



ROHS Conform

**Dimensions and weights**

Net weight 143.5 g

**Environmental Product Compliance**

RoHS Compliance Status Compliant  
 RoHS Exemption (if applicable/known) 7cl  
 REACH SVHC No SVHC above 0.1 wt%  
 SCIP b05b5 122-6117-4cb0-b28c-df32f921fa36

**Technical data**

Description of article Continuity testers

**Measuring and testing devices**

AC voltage measuring range	0.1 - 400 V	Display	Visual & acoustic
Protection degree	IP44	Battery type	1.5 V type AAA battery
Continuity test	Yes - optical + buzzer	Tested and approved according to	DIN EN 61010-1

**Classifications**

ETIM 6.0	EC000494	ETIM 7.0	EC000494
ETIM 8.0	EC000494	ETIM 9.0	EC000494
ETIM 10.0	EC000494	ECLASS 9.0	27-20-03-08
ECLASS 9.1	27-20-03-08	ECLASS 10.0	27-20-03-08
ECLASS 11.0	27-20-03-08	ECLASS 12.0	27-20-03-08
ECLASS 13.0	27-20-03-08	ECLASS 14.0	27-20-03-08
ECLASS 15.0	27-20-03-08		

**VT CTL**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

**Drawings**

[www.weidmueller.com](http://www.weidmueller.com)

