

Data Sheet | Item Number: 733-130

Operating tool; made of insulating material; 1-way; loose; white

<https://www.wago.com/733-130>



Color: ■ white

Technical data

Number of spacings	1 -times
--------------------	----------

Physical data

Depth	18.75 mm / 0.74 inches
Pin spacing	2.5 mm

Mechanical data

Suitable	for male and female connectors with CAGE CLAMP® connection
----------	--

Material data

Color	white
Material group	I
Insulation material (main housing)	Glass fiber-reinforced polyamide (PA66 GF)
Flammability class per UL94	HB
Fire load	0.006 MJ
Weight	0.2 g

Commercial data

Product Group	3 (Multi Conn. System)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454830052
Customs tariff number	82055980000

Product Classification	
UNSPSC	27113201
eCl@ss 10.0	27-44-04-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 8.0	EC002848
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Approvals / Certificates

Approvals for marine applications



Approval	Standard	Certificate Name
LR Lloyds Register	IEC 61984	96/20035 (E5)

Downloads

Environmental Product Compliance


Compliance Search	
Environmental Product Compliance 733-130	↓

CAD/CAE-Data

CAD data	
2D/3D Models 733-130	↓

CAE data	
ZUKEN Portal 733-130	↓

Installation Notes



Conductor termination via operating tool (733-191)

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com