



Color: ■ yellow

Technical data	
Number of spacings	1 -times

Physical data	
Depth	18.75 mm / 0.74 inches
Pin spacing	2.5 mm

Mechanical data	
Suitable	for male and female connectors with CAGE CLAMP® connection

Material data	
Color	yellow
Material group	I
Insulation material (main housing)	Glass fiber-reinforced polyamide (PA66 GF)
Flammability class per UL94	HB
Fire load	0.006 MJ
Weight	0.2 g

Commercial data	
Product Group	3 (Multi Conn. System)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454830069
Customs tariff number	82055980000

UNSPSC	27112809
eCl@ss 10.0	27-44-04-92
eCl@ss 9.0	27-14-11-92
ETIM 9.0	EC002848
ETIM 8.0	EC002848
ECCN	NO US CLASSIFICATION

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals for marine applications



Approval	Standard	Certificate Name
LR Lloyds Register	IEC 61984	96/20035 (E5)

Environmental Product Compliance

Environmental Product Compliance 733-191

CAD data	CAE data
2D/3D Models 733-191	ZUKEN Portal 733-191

Conductor termination via operating tool
(733-191)