

# 2-Port Compact USB KVM Switch with Audio and Cable

MODEL NUMBER: **B004-VUA2-K-R**



2-port Compact USB KVM Switch with optional audio and microphone switching function allows you to access control boot and reboot two USB-enabled computers from a single keyboard monitor and mouse

## Features

- Fast, easy switching via keyboard hot keys, push buttons or software
- Plug-and-play setup - no software required
- Hot-swap capability allows easy addition or removal of computers without powering down the switch or other computers
- Speaker and microphone connections allow sharing of audio components between systems (standard 3.5 mm audio connections)
- Independent audio switching allows you to listen to audio from one computer while switching to the other computer
- Supports video resolutions up to 2048 x 1536 (standard 15-pin VGA connectors)
- Supports Microsoft® IntelliMouse® and the scrolling wheel on most mice]
- Compact design saves desk space
- Does not require an AC adapter
- Compatible with all major operating systems
- Includes two, 6-ft. (1.83 m) Cable Kits

## Highlights

- Fast, easy switching via keyboard hot keys, push buttons or software (not required)
- PC and Mac compatible
- Allows sharing of audio components between systems; listen to music from one computer while switching to the other computer
- Compact design saves desk space
- No AC adapter required
- (x2) 6-ft. (1.83 m) USB KVM Cable kits and (x2) 6-ft. (1.83 m) 3.5mm Audio Cable kits included
- Compatible with all major operating systems

## System Requirements

- Console: VGA, SVGA or Multisync Monitor, USB Keyboard and USB Mouse
- Computers: VGA, SVGA or Multisync Monitor Port and USB Port
- Audio (Optional): Speakers with standard 3.5 mm Connectors and a computer with 3.5mm ports
- Compatible with all major operating systems

## Package Includes

- Compact 2-port USB KVM Switch with Audio
- (2) 6-ft. (1.83 m) USB KVM Cable Kits and (2) 6-ft. (1.83 m) 3.5mm Audio Cable Kits
- Owner's Manual with Warranty Information

## Specifications

| OVERVIEW     |              |
|--------------|--------------|
| UPC Code     | 037332140043 |
| Product Type | KVM          |
| Console      | No           |
| Max CPU      | 1            |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                |                                                                 |
|--------------------------------|-----------------------------------------------------------------|
| Technology                     | VGA/SVGA; Stereo Audio                                          |
| Host Connector                 | (2) USB A (FEMALE)                                              |
| <b>VIDEO</b>                   |                                                                 |
| Video Input                    | HD15 (FEMALE)                                                   |
| Video Output                   | HD15 (FEMALE)                                                   |
| Number of Monitors Supported   | 1                                                               |
| Video Ports                    | (3) HD15 (FEMALE)                                               |
| Max Supported Video Resolution | 2048 x 1536 @60Hz                                               |
| <b>AUDIO</b>                   |                                                                 |
| Audio Ports                    | (2) 3.5MM (FEMALE)                                              |
| Audio Ports Details            | Connect a microphone and speaker via the dual 3.5mm audio ports |
| Audio Input                    | 3.5mm                                                           |
| Audio Output                   | 3.5mm                                                           |
| Audio Specification            | Stereo Audio                                                    |
| <b>DATA</b>                    |                                                                 |
| Data Ports                     | (2) USB A (FEMALE)                                              |
| Data Ports Details             | (2) USB-A - USB 2.0                                             |
| <b>INPUT</b>                   |                                                                 |
| Bus Powered                    | Yes                                                             |
| Power Source                   | Bus; USB                                                        |
| <b>POWER</b>                   |                                                                 |
| Power Consumption (Watts)      | 0.5                                                             |
| <b>CONNECTIONS</b>             |                                                                 |
| Number of Ports                | 2                                                               |
| Daisy-Chain Port               | No                                                              |
| Firmware Upgrade Port          | No                                                              |
| PC/Server Connections          | USB; VGA                                                        |
| Side A - Connector 1           | (2) HD15 (FEMALE)                                               |
| Side B - Connector 1           | HD15 (FEMALE)                                                   |
| Side B - Connector 2           | (2) USB A (FEMALE)                                              |
| Side B - Connector 3           | (2) 3.5MM (FEMALE)                                              |
| Side B - Connector 4           | (2) USB MINI-B 5-PIN (FEMALE)                                   |



Powering Business Worldwide

TRIPP LITE  
SERIES

|                                              |                             |
|----------------------------------------------|-----------------------------|
| Included Cable (Side A) - Connector 1        | Yes                         |
| Computer Keyboard and Mouse Interface        | USB                         |
| Computer Monitor Interface                   | VGA                         |
| Console Keyboard and Mouse Interface         | USB                         |
| Console Monitor Interface                    | VGA                         |
| Connector Plating                            | Nickel                      |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |                             |
| LED Indicators                               | Green (Selected PC)         |
| <b>PHYSICAL</b>                              |                             |
| Color                                        | Black                       |
| Material of Construction                     | ABS                         |
| Cable Jacket Color                           | Black                       |
| Total Number of Ports                        | 9                           |
| Shipping Dimensions (hwd / in.)              | 3.00 x 7.90 x 7.80          |
| Shipping Dimensions (hwd / cm)               | 7.62 x 20.07 x 19.81        |
| Shipping Weight (lbs.)                       | 1.80                        |
| Shipping Weight (kg)                         | 0.82                        |
| Unit Dimensions (hwd / in.)                  | 3.000 x 7.900 x 7.800       |
| Unit Packaging Type                          | Box                         |
| Unit Weight (lbs.)                           | 0.22                        |
| Unit Weight (kg)                             | 0.10                        |
| <b>ENVIRONMENTAL</b>                         |                             |
| Operating Temperature Range                  | 32° to 104°F (0° to 40°C)   |
| Storage Temperature Range                    | -4° to 140°F (-20° to 60°C) |
| Relative Humidity                            | 0-90% non-condensing        |
| BTUs                                         | 1.7 BTU/Hr                  |
| ESD Protection                               | Yes                         |
| <b>COMMUNICATIONS</b>                        |                             |
| Hotkey                                       | Yes                         |
| IP Remote Access                             | No                          |
| EDID Compatible                              | Yes                         |
| IR Remote Extension Support                  | No                          |



Powering Business Worldwide

TRIPP LITE  
SERIES

| FEATURES & SPECIFICATIONS           |                                     |
|-------------------------------------|-------------------------------------|
| USB Hub Ports                       | Yes                                 |
| USB Specification                   | USB 2.0 (up to 480 Mbps)            |
| NIAP-Certified Secure               | No                                  |
| Number of Users                     | 1                                   |
| Autoscan (Y,N)                      | Y                                   |
| On-Screen Display (OSD)             | No                                  |
| Port Selection                      | Pushbutton; Hotkey; Software        |
| Driver Required                     | No                                  |
| Autoscan Duration                   | 10 - 60 seconds                     |
| STANDARDS & COMPLIANCE              |                                     |
| Product Compliance                  | RoHS; CE (Europe); REACH; FCC (USA) |
| WARRANTY & SUPPORT                  |                                     |
| Product Warranty Period (Worldwide) | 3-year limited warranty             |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.