

## 8 Port unmanaged Gigabit Switch 8 PoE Ports IP20 metal

Art.No.: 58193

Weight: 0.7

Country of origin: TW

Model designation: TREE 8TX 8PoE GE

8 Port Unmanaged IP20 PoE Gigabit Switch

24 V power supply

8 PoE ports

### Link to Product

#### Illustration



Product may differ from Image



#### Commercial data

URL Webshop	<a href="https://shop.murrelektronik.com/58193">https://shop.murrelektronik.com/58193</a>
GTIN	4048879844208
ECLASS-6.1	19170106
ECLASS-7.0	19170106
ECLASS-7.1	19170106
ECLASS-8.0	19170106
ECLASS-8.1	19170106
ECLASS-9.0	19170402
ECLASS-9.1	19170106
ECLASS-10.0.1	19170402
ECLASS-10.1	19170402
ECLASS-11.0	19170402
ECLASS-11.1	19170402
ECLASS-12.0	19170402
ECLASS-13.0	19170402
ECLASS-14.0	19170402
EAN	4048879844208

#### Electrical data | Supply

Operating voltage DC min.	12 V
Operating voltage DC max.	57 V

The information in this Product-PDF has been compiled with the utmost care.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2025-10-20

Murrelektronik Inc. | 1327 Northbrook Parkway, Suite 460 | Suwanee, GA 30024 | Fon +1 770 497-9292 | Fax +1 770 497-9391 | [shop@murrinc.com](mailto:shop@murrinc.com) | [shop.murrinc.com](http://shop.murrinc.com)

PoE voltage amplifier	yes
-----------------------	-----

**Industrial communication**

Data transmission rate max.	1,000 MBit/s
-----------------------------	--------------

**Industrial communication | Ethernet functionality**

VLAN unmanaged (IEEE 802.1Q)	no
------------------------------	----

Switch type	unmanaged
-------------	-----------

duplex	Full duplex
--------	-------------

Auto-negotiation	yes
------------------	-----

Auto-crossover	yes
----------------	-----

**Diagnostics**

Alarm contact	yes
---------------	-----

Diagnostic	No voltage
------------	------------

LED display	Ethernet connection/data traffic
-------------	----------------------------------

**Device protection | Electrical**

Degree of protection (EN IEC 60529)	IP20
-------------------------------------	------

**Mechanical data | Material data**

Material housing	Metal
------------------	-------

Color housing	black
---------------	-------

**Mechanical data | Mounting data**

Height	145 mm
--------	--------

Width	57.8 mm
-------	---------

Depth	113 mm
-------	--------

Mounting method	geschnappt
-----------------	------------

Suitable for mounting type	Mounting rail TH35, (EN 60715)
----------------------------	--------------------------------

**Environmental characteristics | Climatic**

Operating temperature min.	-40 °C
----------------------------	--------

Operating temperature max.	70 °C
----------------------------	-------

Storage temperature min.	-40 °C
--------------------------	--------

Storage temperature max.	85 °C
--------------------------	-------

**Connection type 2**

Connection type 1	8
-------------------	---

Connection type 2	X1
-------------------	----

Family construction form	RJ45
--------------------------	------

No. of poles	8
--------------	---

Gender	female
--------	--------

Color contact carrier	black
-----------------------	-------

PIN 1	TD +
-------	------

PIN 2	TD -
-------	------

PIN 3	RD +
-------	------

PIN 4	n.c.
-------	------

PIN 5	n.c.
-------	------

PIN 6	RD -
-------	------

PIN 7	n.c.
-------	------

PIN 8	n.c.
-------	------

Family construction form	terminal
--------------------------	----------

No. of poles	7
--------------	---

Gender	male
--------	------

Color contact carrier	green
-----------------------	-------

Connection	Plug-in terminals RK
------------	----------------------

PIN 1	FE
-------	----

PIN 2	V 1 -
-------	-------

PIN 3	V 1 +
PIN 4	Relay (NO)
PIN 5	Relay (NO)
PIN 6	V 2 -
PIN 7	V 2 +