

## Anybus Communicator – Serial Master to DeviceNet

Item number: AB7001-C

The Anybus Communicator – Serial Master to DeviceNet converts serial protocols to DeviceNet, enabling you to connect any RS-232/485 device or equipment to DeviceNet control systems. Anybus Communicators ensure reliable, secure, high-speed data transfers between different industrial networks while being easy to use.



*A protocol converter that connects serial devices to DeviceNet control systems.*

### Features and benefits

- ✓ **No hardware or software changes needed**  
Integrate your serial RS-232/422/485 based industrial devices and equipment to a PROFIBUS control system without the need for any changes to the device. Just connect, configure and you're done!
- ✓ **Compatible**  
Convert any standard serial protocol such as Modbus RTU, DF1, or any other Request/Response or Produce/Consume proprietary protocol, in just a few minutes.
- ✓ **3-year warranty**  
The Communicator is designed to be robust and long-lasting. A 3-year guarantee is provided.
- ✓ **Convert standard and proprietary serial protocols**  
Convert standard serial protocols such as Modbus RTU and proprietary serial request/response or produce/consume-based protocols.
- ✓ **Daisy chaining**  
Versions with Dual Port switched Ethernet allow for daisy chaining and eliminate the need for external switches.
- ✓ **Life cycle management**  
HMS maintains every part of the Communicator, including network updates, throughout the product's lifecycle.
- ✓ **Hassle-free Connection to Modbus RTU**  
Pre-defined for Modbus RTU. Avoid the hassle of scripting and building serial Modbus frames with the 6-step Modbus RTU wizard.
- ✓ **Slim hardware design**  
The Communicator is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.
- ✓ **Increased PLC Performance**  
The Communicator performs an intelligent protocol conversion and presents the serial data to the PLC control system as easily processed I/O data.
- ✓ **Save & Load**  
The Save/Load function enables a completed configuration to be re-used for other installations.
- ✓ **Trusted partner**  
Anybus has a long history of working with all the major network organizations to ensure compliant, high-performing, and compatible products.

# Anybus Communicator – Serial Master to DeviceNet



General	
Net Width (mm)	27
Net Height (mm)	120
Net Depth (mm)	75
Net Weight (g)	300
Packed Width (mm)	15
Packed Height (mm)	6
Packed Depth (mm)	17
Packed Weight (g)	300
Operating Temperature °C Min	0
Operating Temperature °C Max	55
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Relative Humidity	0-95% non condensing
Current Consumption Type Value at Vcc Nom (mA)	100mA @ 24V DC
Current Consumption Max value at Vcc nom (mA)	300mA @ 24V DC
Input Voltage (V)	24V DC (-10% to +10%)
Power Connector	2-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes



# Anybus Communicator – Serial Master to DeviceNet

## General

Isolation	TRUE
Maximum Installation Altitude (m)	up to 2 000 m
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	PC ABS, UL 94
Packaging Material	Cardboard

## Identification and Status

Product ID	AB7001-C
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	5A991.b.3

## Physical Features

Connectors / Input / Output	1x D-sub 9-pin female, 1x 5-pin, 5.08 Phoenix plug connector
DIP & Rotary Switches	1x 8-dip switch DEV MacID + Baud rate
Contains Battery	No

## DeviceNet Features

DeviceNet Mode	Adapter / Slave
DeviceNet Configuration File	EDS available
DeviceNet Baud Rate	125-500 kbit/s
DeviceNet Input Data Size	512 bytes
DeviceNet Output Data Size	512 bytes

## Modbus-RTU Features

Modbus-RTU Mode	Client / Master
-----------------	-----------------



# Anybus Communicator – Serial Master to DeviceNet

## Modbus-RTU Features

<b>Modbus-RTU Supported Functionality</b>	RS-232; RS-422; RS485; DF1; Standard Modbus RTU Master; Custom Request / Responce commands; Custom Produce / Consume transactions; Trigger initiated transactions 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze
<b>Modbus-RTU Functions Supported</b>	1, 2, 3, 4, 5, 6, 7, 8, 11, 12, 15, 16, 17, 20, 21, 22, 24
<b>Modbus-RTU Baud Rate</b>	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600 bit/s
<b>Modbus-RTU Input Data Size</b>	512 bytes
<b>Modbus-RTU Output Data Size</b>	512 bytes

## Serial Features

<b>Connector</b>	1x D-sub 9-pin female
<b>Max Nodes</b>	31
<b>Baud Rate</b>	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600 bit/s
<b>Supported Functionality</b>	RS-232; RS-422; RS485; DF1; Standard Modbus RTU Master; Custom Request / Responce commands; Custom Produce / Consume transactions; Trigger initiated transactions 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze

## Certifications and Standards

<b>Protection Class IP</b>	IP20
<b>RoHS Compliant</b>	Yes
<b>Recycle / Disposal</b>	TRUE
<b>CE</b>	Yes
<b>FCC</b>	No
<b>UL</b>	Yes
<b>UL Information</b>	E214107: Ord.Loc UL508, CSA C22.2 No. 14-10; E203225: Haz.Loc CL I DIV2 GP A,B,C,D, ANSI/ISA 12.12.01, CSA C22.2 No. 213
<b>EMC</b>	Yes
<b>Environment</b>	EN 50082-2, EN 55011, EN 61000-6-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6
<b>Waste Certification (WEEE)</b>	Yes





# Anybus Communicator – Serial Master to DeviceNet

## Certifications and Standards

WEEE Category

IT and telecommunications equipment