4 Port USB to RS232 Serial DB9 Adapter Hub - TAA

Product ID: ICUSB2324

This 4 Port USB to RS232 Serial Hub lets you connect up to four RS232 serial devices to your Mac or PC laptop or desktop computer through a single USB port, as though the computer offered built-on DB9M serial connectors.

The RS232 Serial Hub is compactly designed to preserve valuable workspace, and is bus-powered to eliminate the need for an external power adapter.

A cost-effective solution that bridges the compatibility gap between modern USB-capable computers and legacy RS232 serial peripherals, this dependable USB/RS232 Serial Adapter hub is backed by StarTech.com's Lifetime Warranty.

Certifications, Reports and Compatibility

RoHS Compliant | WEEE/GK00E3TV | TAA COMPLIANT | CE | FC | (compliance mark)

Windows 11 | Windows 10 | Windows 8 | Windows 7 | Windows Server 2022 | Windows Server 2019 | Windows Server 2016 | Windows Server 2012 | macOS Sonoma

macOS Ventura | macOS Monterey | macOS Big Sur | macOS Catalina | macOS Mojave | macOS High Sierra | macOS Sierra | Linux

Applications

• Connect modems, digitizer tablets, mice, bar code scanners, GPS receivers, ISDN terminal adapters, mobile

phones, scanners, UPSes and POS equipment to your system

• Connect and program LED and Digital signage boards with serial communication ports

Features

• Provides you with four additional RS232 serial ports

• Fully compliant with USB 1.1 specifications and compatible with USB 2.0

• Easy Plug-and-Play installation

• Bus powered, no external power adapter required

Hardware

	Warranty	Lifetime
	Ports	4
	Interface	Serial
	Bus Type	USB 2.0
	Port Style	External Hub
	Industry Standards	RS232
		USB 1.1
	Chipset ID	FTDI - FT232RL

Performance

	Serial Protocol	RS-232
	Max Baud Rate	921.6 Kbps
	FIFO	256 Bytes

Connector(s)

	Connector Type(s)	1 - USB 2.0 Type-A (4 pin, 480Mbps)
	External Ports	4 - DB-9 (9 pin, D-Sub)

Software

	OS Compatibility	Windows CE (4.2, 5.0, 6.0), XP Embedded, 98SE, 2000, XP, Vista, 7, 8, 8.1, 10, 11, 11 ARM
		Windows Server 2003, 2008 R2, 2012, 2012 R2, 2016, 2019,

2022

macOS 10.6 to 10.15, 11.0, 12.0, 13.0, 14.0, 15.0

Linux Kernel 3.0.x and up - LTS Versions only

Special Notes / Requirements		
	System and Cable Requirements	One free USB port

Power		
	Power Consumption (In Watts)	1 ~ 1.5W

Environmental		
	Operating Temperature	0C to 55C (32F to 131F)
	Storage Temperature	-20 to 85C (-4 to 185F)
	Humidity	5~95% RH

Physical Characteristics		
	Color	Black
	Material	Plastic
	Cable Length	6.0 ft [1.8 m]
	Product Length	5.9 in [15 cm]
	Product Width	2.6 in [6.6 cm]
	Product Height	1.0 in [2.6 cm]
	Weight of Product	5.2 oz [146 g]

Packaging Information		
	Package Quantity	1
	Package Length	8.5 in [21.6 cm]
	Package Width	5.9 in [15 cm]
	Package Height	2.0 in [5.2 cm]
	Shipping (Package) Weight	13.0 oz [368.0 g]

What's in the Box

	Included in Package	1 - 4 Port Serial Hub
		1 - USB Cable
		1 - Mounting Bracket
		1 - Driver CD
		1 - Instruction Manual

Warranty Information

	Warranty	Lifetime

*Product appearance and specifications are subject to change without notice.