



Product: [OpEdge-8D](#) 

Industrial Edge Gateway Device for DIN Rail Mounting

Product Description

The Hirschmann OpEdge-8D is an industrial-grade, DIN rail mount edge gateway device that brings edge computing capability to automation infrastructure for processing the large volumes of operational data generated in today's highly connected industrial environments.

Technical Specifications

Product description

Type:	OpEdge-8D
Name:	OpEdge-8D
Part Number:	942330001
Port Type and Quantity:	7 ports in total: 5 x Gigabit Ethernet RJ45 LAN + 2 x Gigabit Ethernet SFP WAN
Port Speed:	10/100/1000 Mbit/s RJ45, 1000 Mbit/s SFP

More Interfaces

USB interface:	2 x USB 3.0 socket to connect an approved USB storage device
Serial:	2 x DB9 serial interfaces for RS232 protocols
Serial Interface:	2 x DB9 serial interfaces for RS232 protocols
Power Supply:	1 x plug-in terminal block, 6-pin

Hardware

Bypass:	2 x Gigabit Ethernet Copper (2 x 1) with Gen3 Bypass
CPU:	Intel Atom E3950 @ 1.6GHz
Encryption:	TPM 2.0 (Trusted Platform Module)
Memory:	DDR3L 8GB
Storage:	64GB SSD storage

Power requirements

Operating Voltage:	Dual 20 ~ 54 V DC
Power consumption:	max. 25 W
Power output in BTU (IT)/h:	58 Btu (IT)/h

Security features

Multipoint VPN:	External connectivity via OpenVPN, IPsec or Belden Horizon™ console
-----------------	---

Service

Protocols:	SNMPv3, HTTPS, SSL-VPN, L2TP, Ping, NTP (Client/ Server), DNS, Dynamic DNS, DHCP (Server/Client)
------------	--

Software

Redundancy:	Routing between LAN and WAN, WAN Backup
Management:	Local Web UI for configuration, diagnostics and maintenance, Supports FTP/SFTP through Belden Horizon™ console
Diagnostics:	LEDs (Power, Link Status, Data, Status), Signal Contact (24 V DC/1 A), Log File
Configuration:	Web Interface, Belden Horizon™ Console

Security:	Integrated Firewall Allowed IP List to prevent unwanted access Secure Socket Tunneling Protocol (SSTP, port 443) with single use credentials to create tunnels AES-256 bit encryption Activity Logs Additional IT-friendly security features when using Belden Horizon™ Console (formerly ProSoft Connect™, a secure, cloud-native platform for the Industrial Internet of Things): • Virtual Lockout, Tagout (vLOTO™) – dynamic authorization for secure remote access • Active Directory support via Single Sign On (SSO) with SAML 2.0 • Email and Token based multi factor authentication • Role based access for users and devices • Configure password rules and enforcement policies • Audit trail with auto-backup
Miscellaneous:	NTP Client and Server, DHCP Client, DNS Client
Routing:	Routing between LAN and WAN, WAN Backup, IP masquerading, 1-to-1 NAT, port forwarding, L2 bridging
Application Support and Management:	Docker Containers, Virtual Machines, App orchestration through Belden Horizon™ console

Ambient conditions

MTBF (Telcordia SR-332 Issue 3) @ 25°C:	387,288 hours
Operating temperature:	-40-+70 °C
Note:	cold start at -20°C
Minimum Storage Temperature:	-40-+85 °C
Relative humidity (non-condensing):	5-95 %

Mechanical construction

Dimensions (WxHxD):	65 x 186 x 160 mm
Weight:	1560 g
Housing Material:	Rugged high-strength sheet metal
Mount Type:	DIN Rail 35 mm
Protection class:	IP40

EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD):	± 4 kV contact discharge; ± 8 kV air discharge
EN 61000-4-3 electromagnetic field:	10 V/m (80 MHz-1000 MHz); 3 V/m (1.4 GHz-6.0 GHz)
EN 61000-4-4 fast transients (burst):	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage:	power line: ± 1 kV (line/ground) and ± 0.5 kV (line/line); data line: ± 1 kV (line/ground)
EN 61000-4-6 Conducted Immunity:	10 V (150 kHz-80 MHz)

EMC emitted immunity

EN 55032:	EN 55032 Class A
FCC CFR47 Part 15:	FCC 47CFR Part 15, Class A

Approvals

Basis Standard:	CE, FCC
Safety of information technology equipment:	UL 62368-1
Shipbuilding:	DNV
Substation:	EN 61850-3, IEEE 1613

Reliability

Guarantee:	60 months (please refer to the https://assets.belden.com/m/1424ddb7a3280e7a/original/Hirschmann-Automation-and-Control-GmbH-Terms-of-Guarantee.pdf terms of guarantee for detailed information)
------------	---

Scope of delivery and accessories

Scope of delivery:	1 × Device, 2 × DIN Rail Kit
--------------------	------------------------------

Further Instructions

Product Documentation:	https://www.doc.hirschmann.com/index.html
Certificates:	https://www.doc.hirschmann.com/certificates.html
Software Download:	https://my.belden.com/s/downloads

History

Update and Revision:	Revision Number: 0.85 Revision Date: 07-24-2025
----------------------	---

Variants

Item #	Type
942330001	OpEdge-8D

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.