



Data Sheet

Customer: _____

Part No: _____

CL-LDS5630UHR-650-5mW

Sample No: _____

Description: _____

Laser Diode

Item No: _____

Customer			
Check	Inspection	Approval	Date


Features

1. 5630 Packaged
2. High temperature operation
3. single mode lasing
4. Standard optical power output : 5mW (CW)

Applications

1. Laser Module
2. Medical application


External dimensions(Unit : mm) 5.60×3.00×0.80



Notes:

1. Drawings are not to scale
2. All dimensions are all in millimeter
3. All dimensions without tolerance are for reference only


Soldering Conditions(Reference Outline)



NOTE : All dimensions in mm tolerance is +/- 0.1mm unless otherwise noted.

The drawing above shows the recommended solder pad layout on Printed Circuit Board (PCB).

Emission direction



Absolute Maximum Ratings


Parameter	Symbol	Rating	Unit
Optical Output ($T_c=25^\circ\text{C}$)	Po	5	mW
LD Reverse Voltage ($T_c=25^\circ\text{C}$)	Vr_LD	2	V
Operating Temperature (Case)	Top	-10~+60	$^\circ\text{C}$
Storage Temperature	Tstg	-40~+85	$^\circ\text{C}$

Electrical and Optical Characteristics(Tc=25°C)


Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit	
Threshold Current	I _{th}	P _o =1-4mW	-	11	15	mA	
Operating Current	I _{op}	P _o =5mW	-	18	23	mA	
Operating Voltage	V _{op}	P _o =5mW	-	2.2	2.5	V	
Slope Efficiency	η	P _o =1-4mW	0.5	0.8	-	mW/mA	
Beam Divergence (FWHM)	Parallel	θ _{//}	P _o =5mW	5	8	12	deg.
	Perpendicular	θ _⊥	P _o =5mW	30	36	42	deg.
Lasing Wavelength	λ	P _o =5mW	640	650	665	nm	

© θ_{//} and θ_⊥ are defined as the angle within which the intensity is 50% of the peak value.


Typical characteristic curves




Forward Voltage v.s. Forward Current




Peak Wavelength v.s. Case Temperature




Far-Field Pattern




Slope Efficiency v.s. Case Temperature





Threshold Current v.s. Case Temperature



Power v.s. Case Temperature




Radiation Pattern in Polar Coordinate System



Packing Information

- Embossed Tape Dimension



■ Precautions

QUALITY ASSURANCE

After any processing of laser chip or laser diode SMD (LD) by the customer, the performance, yield and reliability of the product, in which the chip or LD is applied, are subject to change due to customer's handling, assembly, testing, and processing. Because laser chip and LD are strongly affected by environmental conditions, physical stress, and chemical stresses imposed by customer that are not in Ciellight Corp. control and hence no guarantee on the characteristics and the reliability at all after the shipment. Also, CL does not have any responsibility for field failures in a customer product. When attaching a heat sink to laser chip or LD, be careful not to apply excessive force to the device in the process.

SAFETY PRECAUTIONS

Although Ciellight Corp. keeps improving quality and reliability of its laser chip and laser diode SMD (LD), semiconductor devices in general can malfunction or fail due to their intrinsic characteristics. Hence, it is required that the customer's products are designed with full regard to safety by incorporating the redundancy, fire prevention, error prevention so that any problems or error with CL laser chip or LD does not cause any accidents resulting in injury, death, fire, property damage, economic damage, or environmental damage. In case customer wants to use CL laser chip or LD in the systems requiring high safety, customer is requested to confirm safety of entire systems with customer's own testing.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

The information provided by Ciellight Corp., including but not limited to technical specifications, recommendations, and application notes relating to laser chip or laser diode SMD (LD) is believed to be reliable and accurate and is subject to change without notice. CL reserves the right to change its assembly, test, design, form, specification, control, or function without notice.