







CIXI WANJIE ELECTRONIC CO., LTD

product specification



P.C.B.LAYOUT



Electrical

Standard	UL	IEC
Rated voltage	300V	750V
Rated current	52A	57A
Contact resistance	20mΩ	
Insulation resistance	5000MΩ/DC1000V	
Wire range	20-6AWG 10.0mm ²	
Withstanding voltage	AC 3000V/1 Min	

Mechanical

Temp.Range	-40℃~+105℃
MAX Soldering	+250℃ for 5 Sec
Torque	1.2Nm(10.5lb.in)
Strip length	10mm

Dimensions

Pitch	10.16mm
Poles	1p. xxp

Material

Housing	PA66,UL94V-0
Screws	M4 steel Zinc plated
Pin housing	Brass,Tin plated
Clamp	Brass, Ni plated

TOLERANCES EXCEPT AS NOTED

	linear dimension					fillet	chamfer	short angle sid	≡	—	□	//	⊥
variable range	to 6	over 6 to 30	over 30 to 120	over 120 to 480	over 480 to	all	to 6	to 10	to 10	to 50	to 120	to 10	to 120
tolerance	±0.1	±0.2	±0.3	±0.5	±0.9	±0.2	±0.5	±1	1°	30'	20'	10'	0.5

UNITS


mm

SIZE

A4

SCALE

FIRST ANGLE PROJECTION



CIXI WANJIE ELECTRONIC CO., LTD

NAME

WJ116V-10.16