


Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权,否则禁止转让、复制、利用、交流本文档的内容。侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。



REVISION RECORD							
REV.	ESCRIPTION			ECN No.	APPROVED	DATE	
0	新发行				YaoFei	24.02.27	
				UL/CUL 技术参数 UL/CUL Technical Data			
				等级 Use Group	B	C	
额定电压 Rated Voltage [V]				150	-	-	
额定电流 Rated Current [A]				5	-	-	
接线范围 Wire Range 单/多芯线 Solid/Stranded [AWG]				26-20			
耐电压 Withstanding Voltage				1300V/1Min			
IEC 技术参数 IEC Technical Data				IEC61984			
过电压类别 Overvoltage Category				III	III	II	
污染等级 Contamination Class				3	2	2	
额定电压 Rated Voltage [V]				100	160	320	
额定电流 Rated Current [A]				5	5	5	
额定冲击电压 Impulse withstand voltage [KV]				1.5	2.5	2.5	
导线截面积 Conductor cross section 硬质/柔性导线 Solid/ flexible [mm²]				0.2-0.5			
一般参数 Other Data							
间距 Pitch /极数 Poles [mm]/[P]				2.5 / 02-24			
剥线长度 Stripping Length [mm]				7~8			
工作温度 Operating temperature [°C]				-40~105			
符合RoHS环保要求							

S.	YaoFei	DATE	24.02.27	UNITS	mm	THIRD ANGLE PROJECTION		
K.	YangHJ	DATE	24.02.27	SIZE	A4	TYPE: CUSTOMER DRAWING	SHEET 1 of 1	
P.	JASON	DATE	24.02.27	SCALE	2:1	DRAWING TYPE: SP-03	REV	0



慈溪市万捷电子有限公司
CIXI WANJIE ELECTRONIC CO., LTD

PART NO.:
WJ15EDGKD-2.5-XXP-1Y-00A

General Tolerances								—		
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

5	Button	POM	UL94-HB
4	Spring	Stainless Steel	
3	Clamp	Copper Alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES