






CIXI WANJIE ELECTRONIC CO., LTD

THE SPEC SHEET



P.C.B. LAYOUT



UL/CUL Technical Data		UL		
Use Group		B	C	D
Rated Voltage [V]		300	—	300
Rated Current [A]		8	—	8
Wire Range		/		
Solid/Stranded [AWG]		/		
Withstanding Voltage		1600V/1Min		
IEC Technical Data		IEC 61984		
Overvoltage Category		III	III	II
Contamination Class		3	2	2
Rated Voltage [V]		160	160	250
Rated Current [A]		8	8	8
Impulse withstand voltagea [KV]		2.5	2.5	2.5
Conductor cross section		/		
Solid/ flexible [mm²]		/		
Material				
Insulation Material		LCP		
Inflammability		UL94V-0		
Contact Material		Copper alloy		
Contactive Coating		Sn Plated		
Other Data				
Pitch [mm]		3.5		
Poles [P]		2*02-2*24		
Stripping Length [mm]		/		
Screw		/		
Torque(Max) [N.m]		/		
Operating temperatur [°C]		-40~130		


linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to 10	over 10 to 100	over 100 to 100
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30

UNITS mm SIZE A4 SCALE 3:1

THIRD ANGLE PROJECTION



CIXI WANJIE ELECTRONIC CO., LTD

TITLE

WJ15EDGVHC-THR-3.5-2*XXP-1YY-00A