



product specification

Standard: UL IEC

Rated voltage: 300V 750V

Rated current: 20A 32A

Wire range: 22-12AWG 4.0mm²

Withstanding voltage: AC2000V/1Min

Insulation resistance: 500M Ω /DC500V

Temp.Range: -40°C to $+105^{\circ}\text{C}$

Max. T.alue: 1. 7Nm (15lb. in)

Pitch: 9.5mm

Poles: $2P-24P$

Housing: PA66, UL94V-0

Screws: M4, steel Nickel plated

Pin header: Brass, 0.8t, Tin plated



Diagram illustrating the decomposition of a 2x2 grid into four 1x1 grids, with a central 'P' and a vertical line.

X	X	X
客户	需求	
Customer	Request	

—

X	X	X	X
Customer Request			
灰色/Grey	10	綠色/Green	40
藍色/Blue	20	橘色/Orange	50
黑色/Black	30	紅色/Red	60
透明/Transparent	70	黃色/Yellow	80
白色/White	90		

linear dimension

	over	over	over	over		over	over	over	over		over	over	over			
variable range	6 to	30 to	120 to	480 to	all	6 to	10 to	50 to	120 to	all	5 to	30 to	120 to			
tolerance	± 0.1	± 0.2	± 0.3	± 0.5	± 0.9	± 0.2	± 0.5	$\pm 1^*$	$30'$	$20'$	$10'$	0.5	$d_{0.025}$	0.06	0.12	0.4

UNITS	mm	SIZE	A4	SCALE
-------	----	------	----	-------



CIXI WANJIE ELECTRONIC CO., LTD

FIRST ANGLE PROJECTION



NAME | WJ48HM-XXP-1YY-00A

K-00A