





Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权，否则禁止转让、复制、利用、交流本文件的内容。 侵犯者将承担相应责任。 本公司保留对涉及发明、实用新型和外观设计的所有权利。



P.C.B. LAYOUT



REVISION RECORD				
REV.	ESCRPTION	ECN No.	APPROVED	DATE
V0			ZhaoXY	24.04.01

/Electrical	
/Rated voltage	300V
/Rated current	20A
/Contact resistance	20mΩ
/Insulation resistance	500MΩ/DC500V
/Wire range	22~12AWG
/With standing voltage	AC 1600V/1 Min
/Mechanica	
/Torque	1.2Nm(10.6Lb.in)
/Temp.Range	-40°C~+105°C
/MAX Soldering	+260°C, for 5 Sec
/Dimensions	
/Pitch	11mm
/Poles	2~22p

4	Cover	PC	UL94V-2
3	Pin Header	Copper Alloy	Sn Plated
2	Screws	Steel	M4 Steel Ni plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

DES.	ZhaoXY	DATE	24.04.01	UNITS	mm	THIRD ANGLE PROJECTION	
CHK.	HuHT	DATE	24.04.01	SIZE	A4	TYPE: CUSTOMER DRAWING	
APP.	Jason	DATE	24.04.01	SCALE	2:1	DRAWING TYPE: SP-03	
PART NO.: WJ68S-XXP-1Y-00A						REV V1	



CIXI WANJIE ELECTRONIC CO., LTD

FOR-0371 Rev.1.0

General Tolerances								—	∠	⊥
variable range	to 6	over 6 to 10	over 10 to 30	over 30 to 60	over 60 to 100	over 100 to 160	over 160 to	to 10	over 10 to 100	over 100 to
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60