







CIXI WANJIE ELECTRONIC CO., LTD

product specification



Section: A-A



Electrical

Standard	UL	IEC
Rated voltage	300V	250V
Rated current	8A	15A
Contact resistance	20mΩ	
Insulation resistance	5000MΩ/DC1000 V	
Wire range	30-16A WG 1.5mm ²	
Withstanding voltage	AC 2000V/1 Min	

Mechanical

Temp.Range	-40℃ ~+105℃
MAX Soldering	+250℃ for 5 Sec
Torque	0.2Nm(1.7lb .in)
Strip length	5-6mm

Dimensions


Pitch	3.5mm 3.81mm
Poles	2p. xxp

Material

Housing	PA66,UL94V-0
Screws	M2 steel Zinc plated
Pin housing	Brass,Tin plated
Clamp	Brass, Ni plated

TOLERANCES EXCEPT AS NOTED

	linear dimension					fillet	chamfer	short angle sid	≡	—	□	//	⊥
variable range	to 6	over 6 to 30	over 30 to 120	over 120 to 480	over 480 to	all	to 6	to 10	to 10	to 50	to 120	to 10	to 120
tolerance	±0.1	±0.2	±0.3	±0.5	±0.9	±0.2	±0.5	±1	1°	30'	20'	10'	0.5

UNITS	mm	SIZE	A4	SCALE	FIRST ANGLE PROJECTION	
 CIXI WANJIE ELECTRONIC CO., LTD						
					NAME	WJEK350A-3.5 WJEK381A-3.81