

HANGZHOU HUAYANG ELECTRONICS CO.,LTD.

PRODUCT SPECIFICATION

Customer: _____

Customer's Model No.: _____

Customer's Drawing No.: _____

Model No.: CLQ-5643BLUR-11

Drawing No.: _____

Add: No.47 Xiangyuan Road, Hangzhou China

Tel: 86-571-87977022 87979022

Fax: 86-571-85124747

P.C: 310011

E-mail: hy@hz-huayang.com


Http: www.hz-huayang.com



Descriptions


1. Emitting color :Red
2. Lens color:White Diffuse
3. Surface Black color: Black
4. Dice material: AlGaInP/GaAs

Outline drawing



Tolerance is $\pm 0.25\text{mm}$ unless otherwise noted

Internal Circuit Diagram (C.C.)





Electrical optical characteristics (Ta=25℃)





Parameter	Symbol	Red			Unit	Test Condition
		Min	Typ	Max		
Forward Voltage	V _F		2.0	2.3	V	IF=20mA
Luminous Intensity	I _V		30		mcd	IF=10mA
Peak Wavelength	λ _P		640		nm	IF=20mA
Spectral Line half-width	Δλ		20		nm	IF=20mA
Reverse Leakage Current	I _R			50	μA	V _R =5V

Absolute maximum parameters (Ta=25℃)

Parameter	Symbol	Condition	Rating	Unit
Power Dissipation	PD	---	100	mW
Reverse Voltage	VR	---	5	V
Forward Average Current	IF	---	30	mA
Temperature coefficient	I/C	---	0.4	mA/℃
Pulse Current	IFP	Duty=1/10,1kHz	100	mA
Operating Temperature Range	Topr	---	-25 ~ +85	℃
Storage Temperature Range	Tstg	---	-30 ~ +100	℃
Soldering Condition	Tsd	---	265℃/5sec	℃



Typical Electro-Optical characteristic curves ($T_a=25^{\circ}\text{C}$)





Reliability test conditions

Test Item	Test Condition	Result	Judgment criteria
Consecutive operating life test	IF=20mA, T=25℃, t=168h	0/12	Forward Voltage $V_F(V) = \text{Upper Limit} \times 1.2$ Reverse Leakage Current $I_R(\mu A) = \text{Upper Limit} \times 2.0$ Luminous Intensity I_v (mcd)=Lower Limit $\times 0.7$
High temperature storage life test	T=100℃, t=168h	0/12	
Low temperature storage life test	T=-25℃, t=168h	0/12	
high Temperature humidity storage life test	T=85 ± 2℃, RH=85% ± 3, t=168h	0/12	
Temperature cycle test	-25℃~25℃~100℃, 30min 5min 30min 10cycles	0/12	
Thermal shock test	100℃ 0℃ 5min 5min 20 cycles	0/12	
Soldering heat test	T=260 ± 5℃, t=10s ± 1s	0/12	
Solderability test	T=230 ± 5℃, t=5s ± 0.5s	0/12	Steeped Part ≥ 95%
Fall test	h=100cm, Free fall, 3times	0/12	Intact
Terminal strength test	W=9.8N, t=30 ± 5s	0/12	
Lead Bending test	W=4.9N, 2times	0/12	